

6” Submersible Solar Pump, AC110/DC150, AC220/DC300, AC380/DC540, BLA

model	max.flow (m ³ h)	max.head (m)	pump		solar panel		pump diameter (inch)	outlet(inch)
			voltage(v)	power(w)	open circuit voltage(v)	recommended power(kw)		
6BLA25-10-1.1	38	18	AC110/DC150	1.1	180-220	1.6	6	3
6BLA25-14-1.5	38	20	AC220/DC300	1.5	300-450	2.1	6	3
6BLA25-20-2.2	35	30	AC220/DC300	2.2	300-450	2.7	6	3
6BLA45-10-2.2	65	18	AC220/DC300	2.2	300-450	2.7	6	3
6BLA25-30-3	40	45	AC 380/DC 540	3	540-800	4.2	6	3
6BLA60-14-3	85	22	AC 380/DC 540	3	540-800	4.2	6	3
6BLA25-40-4	33	60	AC 380/DC 540	4	540-800	5.5	4	3
6BLA40-18-4	62	32	AC 380/DC 540	4	540-800	5.5	6	3
6BLA80-15-4	95	22	AC 380/DC 540	4	540-800	5.5	6	3
6BLA25-50-5.5	35	75	AC 380/DC 540	5.5	540-800	8	6	3
6BLA45-30-5.5	60	45	AC 380/DC 540	5.5	540-800	8	6	3
6BLA60-25-5.5	80	38	AC 380/DC 540	5.5	540-800	8	6	3
6BLA25-75-7.5	35	100	AC 380/DC 540	7.5	540-800	10	6	3
6BLA45-44-7.5	60	65	AC 380/DC 540	7.5	540-800	10	6	3
6BLA60-34-7.5	80	50	AC 380/DC 540	7.5	540-800	10	6	3
6BLA18-90-7.5	30	120	AC 380/DC 540	7.5	540-800	10	6	3
6BLA30-60-7.5	53	78	AC 380/DC 540	7.5	540-800	10	6	3
6BLA45-44-7.5	75	65	AC 380/DC 540	7.5	540-800	10	6	3
6BLA60-32-7.5	80	55	AC 380/DC 540	7.5	540-800	10	6	3
6BLA18-115-9	30	155	AC 380/DC 540	9	540-800	12.6	6	3
6BLA30-80-9	53	100	AC 380/DC 540	9	540-800	12.6	6	3
6BLA45-52-9	75	80	AC 380/DC 540	9	540-800	12.6	6	3
6BLA60-40-9	80	68	AC 380/DC 540	9	540-800	12.6	6	3
6BLA18-140-11	30	190	AC 380/DC 540	11	540-800	15.75	6	3
6BLA30-100-11	53	135	AC 380/DC 540	11	540-800	15.75	6	3
6BLA45-62-11	75	95	AC 380/DC 540	11	540-800	15.75	6	3
6BLA60-48-11	80	80	AC 380/DC 540	11	540-800	15.75	6	3

6BLA18-190-15	30	245	AC 380/DC 540	15	540-800	21	6	3
6BLA30-120-15	53	160	AC 380/DC 540	15	540-800	21	6	3
6BLA45-88-15	75	130	AC 380/DC 540	15	540-800	21	6	3
6BLA60-64-15	80	110	AC 380/DC 540	15	540-800	21	6	3
6BLA18-240-18.5	30	310	AC 380/DC 540	18.5	540-800	26	6	3
6BLA30-135-18.5	53	180	AC 380/DC 540	18.5	540-800	26	6	3
6BLA45-105-18.5	75	155	AC 380/DC 540	18.5	540-800	26	6	3
6BLA60-72-18.5	80	125	AC 380/DC 540	18.5	540-800	26	6	3
6BLA80-65-18.5	120	120	AC 380/DC 540	18.5	540-800	26	6	3
6BLA30-170-22	53	210	AC 380/DC 540	22	540-800	31.55	6	3
6BLA45-132-22	75	195	AC 380/DC 540	22	540-800	31.55	6	3
6BLA60-95-22	80	160	AC 380/DC 540	22	540-800	31.55	6	3
6BLA30-240-30	53	300	AC 380/DC 550	30	540-800	42	6	3
6BLA45-170-30	75	245	AC 380/DC 540	30	540-800	42	6	3
6BLA60-128-30	80	220	AC 380/DC 540	30	540-800	42	6	3
6BLA80-100-30	120	150	AC 380/DC 540	30	540-800	42	8	5